KP100 SPECIFICATION

CONTROLLER SPECIFICATION

MEASURING RANGE FOR AIR AND N_2	1 ~ 1000 mTorr
OPERATING TEMPERATURE	0 ~ 60 ℃
STORAGE TEMPERATURE	- 40 ~ 70 ℃
CASE MATERIAL	Plastic and Steel
COMPLIANCE	
DISPLAY	103 X 84 , Analoge meter
SET POINT RELAYS	None
ANALOG OUTPUT	None
DIGITAL INTERFACE	None
POWER REQUIRED	AC100~240V, 50/60HZ, 0.8A
WEIGHT	190g
MOUNTING	Pannel moumting

SENSOR SPECIFICATION

SENSOR TYPE	PIRANI Gauge (KVC300 - XX)
SENSOR MATERIALS	Gold Plated Tungsten or Platinum
INTERNAL VOLUME	5 Cm^3
GAUGE BAKEOUT TEMPERATURE	150 ℃ Maximum , NON – operating
CASE MATERIALS	304 Stainless steel, borosilicate glass, Kovar



폭발성 대기상태, 가연성 가스와 증기가 있는 곳에 사용하지 마십시오.



폭발성가스, 가연성가스, 혼합가스의 압력을 측정하기위해 사용하지 마십시오.

SENSOR FILAMENT 는 일반적으로 동작 시 온도가 110 ℃ 입니다.